

BitNami WAPPStack 5.3.10-0

Quick Start Guide

BitNami LAPPStack 5.3.10-0

Release 5.3.10-0 2012-02-06

Copyright © 2007 BitNami

<http://bitnami.org>

All rights reserved.

This product and its documentation are protected by copyright. The information in this document is provided on an "as is" basis, without warranty. Although every precaution has been taken in the preparation of this document, the authors will not have any liability to any person or entity with respect to any loss or damage caused or alleged to be caused directly or indirectly by the information contained in this work.

Trademark names may appear in this document. All registered and unregistered trademarks in this document are the sole property of their respective owners.

Acknowledgements

BitNami WAPPStack is based on a number of open source components:

The Apache HTTP server, developed by The Apache Software Foundation.

<http://www.apache.org/>.

PostgreSQL. The world's most advanced open source database.

<http://www.postgresql.org>

PHP. The widely used scripting language.

<http://www.php.net>.

The open source browser-based PostgreSQL management tool phpPgAdmin.

<http://phppgadmin.sourceforge.net>

jpegsrc. Software developed by the The Independent JPEG Group.

<http://www.ijg.org>

The gd graphics library.

<http://www.boutell.com/gd/>

The zlib data-compression library.

<http://www.zlib.net>

You can find the individual licenses for the above projects as part of the installation.

BitNami WAPPStack Overview

BitNami WAPPStack is an easy to install and easy to use open source Web Platform. It combines leading open source projects, such as Apache, PostgreSQL and PHP with BitNami's extensive open source expertise to provide a consistent, painless way to deploy WAPP in any Windows environment.

Components

BitNami WAPPStack includes **Apache 2.2.21**, **PostgreSQL 9.1.1-1**, **PHP 5.3.10** and **phpPgAdmin 5.0.3**.

Apache is the most popular HTTP server on the Internet. It provides a secure, efficient and extensible web platform. It is maintained by the Apache Software Foundation. You can find more information about Apache at <http://www.apache.org>.

PostgreSQL is a powerful, open source relational database system. It has more than 15 years of active development and a proven architecture that has earned it a strong reputation for reliability, data integrity, and correctness. You can find more information about PostgreSQL at <http://www.postgresql.com>.

PHP is a web development scripting language that can be embedded into HTML. Powerful and easy to use, it is the most popular Apache module. It is maintained by the PHP Group. You can find more information about PHP at <http://www.php.net>.

phpPgAdmin is a tool written in PHP intended to handle the administration of PostgreSQL through a web interface. It allows you to manage anything from a single database to a complete PostgreSQL server. You can find more information about phpMyAdmin at <http://phppgadmin.sourceforge.net/>.

Requirements

To run BitNami WAPPStack you will need:

- Intel x86 or compatible processor
- Minimum of 256 MB RAM
- Minimum of 150 MB hard drive space
- An 32-bit Windows operating system such as Windows 2000, XP, Vista, or Windows 2003 Server
- TCP/IP protocol support

Installation Guide

This section describes where to download BitNami WAPPStack and the different installation modes that are available.

Downloading BitNami WAPPStack

You can download the BitNami WAPPStack binary file from <http://bitnami.org>. It will be named `bitnami-wappstack-5.3.10-0-windows-installer.exe`.

Installing BitNami WAPPStack

You can install BitNami WAPPStack in graphical, text and unattended modes. By default the graphical mode will be used.

Graphical Mode

To begin the installation process, double-click on the file from your Desktop environment or invoke it directly from the command line with:

```
$ bitnami-wappstack-5.3.10-0-windows-installer.exe
```

You will be greeted by the 'Welcome' screen. The next step is to select the installation directory. The default installation path will be `C:\Program Files\Bitnami WAPPStack-5.3.10-0`. If the destination directory does not exist, it will be created as part of the installation.

After selecting the installation directory you will be asked for the password to the initial PostgreSQL root and postgres accounts. This password cannot be empty and it will be used with phpPgAdmin too.

The default listening port for Apache is 80 and for PostgreSQL is 5432. If those ports are already in use by other applications, you will be prompted for alternate ports to use.

You are now ready to begin the installation, which will start when you press 'Next'. Once the installation process has been completed, you will see the 'Installation Finished' page. You can launch the browser at this point.

If you receive an error message during installation, please refer to the Troubleshooting section.

The rest of this guide assumes that you installed BitNami WAPPStack in `C:\Program Files\Bitnami WAPPStack-5.3.10-0` and that you use port 80 for Apache and 5432 for PostgreSQL.

Text Mode

This installation mode is designed for remote installation or installation on servers without X-Window support. It is started by default when a graphical environment is not available or by issuing the following command:

```
$ ./bitnami-lappstack-5.3.10-0-linux-installer.bin --mode text
```

You will be greeted by the 'Welcome' message. The next step is to select the installation directory. The default installation path will be a folder on your home directory if you are running the installer as a regular user, or `C:\Program Files\Bitnami WAPPStack-5.3.10-0`, if you are running the installation as root. If the destination

directory does not exist, it will be created.

After selecting the installation directory you will be asked for the password to the initial PostgreSQL root and postgres accounts. This password cannot be empty.

The default listening port for Apache is 80 and for PostgreSQL is 5432. If those ports are already in use by other applications, you will be prompted for alternate ports to use.

You are now ready to begin the installation process, which will start when you press 'Enter'. Once the installation process has been completed, you will see the 'Installation Finished' message.

Unattended Mode

It is possible to perform an unattended or silent installation using the `--mode unattended` command line option. This is useful for automating installations or for inclusion in shell scripts, as part of larger installation processes. You will not be asked for anything during the installation.

However you will need to pass to the installer the values of the password to the initial PostgreSQL root and anonymous accounts and the initial password to access phpMyAdmin. You can do that using the options `--rootpasswd` and `--phppgadminpasswd`. For example:

```
$ ./wappstack-5.3.10-0-windows-installer.exe --mode unattended --rootpasswd postgresqlpasswd --phppgadminpasswd ppapasswd
```

You can also modify the default installation directory by passing the `--prefix /path/to/installdir` command line option to the installer.

Apache will use by default the port 80 and PostgreSQL the port 5432. You can change those values as well using the command line options `--dbport` and `--webport`:

```
$ ./wappstack-5.3.10-0-windows-installer.bin --mode unattended --rootpasswd postgresqlpasswd --phppgadminpasswd ppapasswd --dbport 5432 --webport 8085
```

Please make sure that the ports you specify are not already in use by other applications.

If you receive an error message during installation, please refer to the Troubleshooting section.

The rest of this guide assumes that you installed BitNami WAPPStack in `C:\Program Files\Bitnami WAPPStack-5.3.10-0` and that you use port 80 for Apache and 5432 for PostgreSQL.

Directory Structure

The installation process will create several subfolders under the main installation directory:

- `apache2/`: Apache Web server.
- `php/`: PHP Scripting Language.
- `postgresql/`: PostgreSQL Database.
- `common/`: common libraries.
- `licenses/`: Licenses of the components included in LAPPStack.
- `apps/phpPgAdmin/`: Management tool for PostgreSQL.

Uninstalling BitNami WAPPStack

As part of the installation, an uninstall program will be created at `C:\Program Files\Bitnami wappstack-5.3.10-0/`. The uninstallation can also be performed in graphical, text and unattended modes. You can run the uninstaller by double-clicking on the uninstall application or through the command line:

```
$C:\Program Files\Bitnami wappstack-5.3.10-0\uninstall.exe
```

Apache Web server

This section describes how to start Apache for the first time and gives a basic introduction to the Apache configuration and log files.

Starting Apache

You can start Apache from the command line by issuing:

```
$ C:\Program Files\BitNami Wappstack-5.3.10-0/ctlscript.sh start apache
```

If no error is found, you will see a message similar to:

```
Syntax OK
```

```
wappstack-5.3.10-0/setuprun.bat : httpd started
```

This indicates the server is up and running. You can test so by opening a browser and accessing the following URL `http://127.0.0.1`, which will take you to the test page.

If you receive an error message, the server cannot start or you cannot see the test page, please refer to the Troubleshooting section.

Stopping Apache

You can stop Apache from the command line issuing:

```
$ C:\Program Files\BitNami Wappstack-5.3.10-0/setuprun.bat stop apache
```

After a moment you should see a message similar to:

```
Syntax OK
```

```
C:\Program Files\BitNami Wappstack-5.3.10-0/setuprun.bat : httpd stopped
```

Apache Basic Configuration

The main Apache configuration file is called `httpd.conf` which you can find at `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/conf/httpd.conf`.

Once Apache starts, it will create two log files, the `access_log` and the `error_log`. You can find both files at the `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/logs` directory.

The `access_log` file is used to track client requests. When a client requests a document from the server, Apache records several parameters associated with the request in this file, such as: the IP address of the client, the document requested, the HTTP status code, and the current time.

The `error_log` file is used to record important events. This file includes error messages, startup messages, and any other significant events in the life cycle of the server. This is the first place to look when you run into a problem when using Apache.

If you already have a web page and you want to serve its content with Apache, you can do so simply by copying your

files to the default document root directory: `/home/user/lappstack-5.3.10-0/apache2/htdocs/`.

With the default configuration, Apache will wait for requests in the port 80. You can change that by editing the `httpd.conf` file and modifying the value specified in the `Port` directive.

You can find more information about Apache in the technical documentation that is located in the `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/htdocs/manual` directory.

PostgreSQL Database

This section describes how to start the PostgreSQL database and gives you a few basic security tips. You can find the PostgreSQL technical documentation at <http://www.postgresql.org/docs/>.

Securing Your Installation

PostgreSQL's grant tables are created during the BitNami WAPPStack installation process. The grant tables define the initial PostgreSQL user accounts and their access privileges. The default configuration consists of a postgres-user account. The initial password of this account is the one that you specified in the setup wizard.

It is strongly recommended that you do not have empty passwords for any user accounts before using the server for any production work.

Starting PostgreSQL

After installing BitNami WAPPStack you can start the PostgreSQL server issuing:

```
$ C:\Program Files\BitNami Wappstack-5.3.10-0/setuprun.bat start postgresql
```

You can verify that PostgreSQL is up and running using psql, for example, issuing:

```
$ C:\Program Files\BitNami Wappstack-5.3.10-0/postgresql/bin/psql.exe
```

You will then be asked for the postgres user password you set during the installation process.

Stopping PostgreSQL

You can shutdown PostgreSQL with the following command:

```
$ C:\Program Files\BitNami Wappstack-5.3.10-0/setuprun.bat stop postgresql
```

PHP

This section describes how to test your PHP installation. You can find the PHP technical documentation at <http://www.php.net/manual/en/index.php>

Testing Your Installation

The easiest way to test your PHP installation is to create a test script using the `phpinfo()` function. Open your favorite text editor and type:

```
<?php phpinfo(); ?>
```

Save the file as `phptest.php` in `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/htdocs/`. Make sure Apache is up and running, open a browser and type `http://127.0.0.1/phptest.php`. You should then see a screen showing detailed information about the PHP version you are using.

phpPgAdmin

This sections describes how to access your phpPgAdmin installation. You can find more information about phpPgAdmin in <http://phppgadmin.sourceforge.net/?page=faq>

phpPgAdmin is an easy to use management tool for PostgreSQL that allows you to create and drop databases, create, drop and modify tables, delete, edit and add fields, execute SQL statements, manage keys on fields, manage privileges and export data in various formats through a web-based interface.

Access to phpPgAdmin

To test your phpMyAdmin installation first make sure that your Apache and PostgreSQL servers are up and running. You can access your phpMyAdmin installation by opening a browser and typing `http://127.0.0.1/phpmyadmin`. You will then asked for a username and password. As user name, use "**administrator**" and as password use the value specified during installation.

Initially only requests from 127.0.0.1 will be allowed access to that section. You can change this behavior editing the Apache main configuration file located at `C:\Program Files\BitNami Wapstack-5.3.10-0/apache2/conf/httpd.conf`.

Troubleshooting

This section describes some of the most common problems you may find when installing BitNami WAPPStack.

Installer

Installer Payload Error

You may get the following error while trying to run the installer from the command line:

```
Installer payload initialization failed. This is likely due to an incomplete or corrupt
downloaded file.
```

The installer binary is not complete, likely because the file was not downloaded correctly. You will need to download the file and repeat the installation process.

Installation does not complete and hangs at the end forever.

You are probably overwriting a previous WAPPStack installation and therefore a previous PostgreSQL with a different PostgreSQL `bnpostgres` password. Remove or move your previous WAPPStack installation and try to install WAPPStack again.

Apache

If you find any problem starting Apache, the first place you should look at is the error log file that will be created at `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/logs/error_log`. There you will likely find useful information to determine what the problem may be. For issues not covered in this Quick Start guide, please refer to the Apache documentation included as part of the installation, which is located at `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/htdocs/manual`.

Test page is not working

If the server seems to start correctly (i.e. you can see the `./apachectl start: httpd started` message) but you cannot see the test page when you type `http://127.0.0.1/` in your browser, it may be that there is already a server running in that port.

Search `C:\Program Files\BitNami Wappstack-5.3.10-0/apache2/logs/error_log` for a message similar to this:

```
[Mon Oct 9 19:52:10 2007] [crit] (98)Address already in use: make_sock: could not bind to port
80
```

This means that the port 80 is already being used by another program. You can either stop the program that is using that port or edit the `httpd.conf` configuration file and change the port Apache will listen for requests in.

Cannot bind to port 80

If you change the default listening port for Apache and get the following error in `error_log`:

```
[Mon Oct 9 20:09:50 2007] [crit] (13)Permission denied: make_sock: could not bind to port 80
```

you do not have enough permissions to bind to that port.

PostgreSQL

If you encounter any problems starting PostgreSQL, the first place to look in is the "Problems and Common Errors" section of the PostgreSQL manual, which you will find at <http://www.postgresql.org/docs/>

The following are some common problems:

Access denied when trying to connect to PostgreSQL.

If you get an `Access Denied` message while trying to connect to PostgreSQL, make sure you are using the correct username and password.

"Can't connect to server" message.

Make sure the PostgreSQL daemon is up and running.